

**Laundry machines**

Tumble Dryers

**Performance specifications**Load capacity: 8kg  
Drum volume: 180l

PT 7186

**Controls**

PROFITRONIC L VARIO, electronic controls with graphic LC display, 15 standard programmes with 4 drying stages, 2 timed drying programmes, 7 optional programme packages, simple programme selection via multi-function selector, 4 direct-access buttons to select Favourites, individual programmes can be saved, multi-language commissioning routine (24 languages available), 24 h delay start, countdown indicator, drum lighting

Full range of programmes, options and temperatures adjustable

Specifically designed for aged care facilities, hotels, motels, etc

**Heating**

Electric (EL)

**Electrical connection**3N AC 400 V 50Hz  
Fuse rating [A]: 3x16  
Rated load [kW]: 8.50  
Heater rating [kW]: 7.90**Features**

Stainless-steel drum  
Large-surface filter with effective area of 0.14 m<sup>2</sup>  
Large double-glazed glass porthole door [~ 44 cm]  
Drum lighting

**Drying technology**

Vented dryer with air recirculation, vent connection DN 100, 2 separate motors for drum and fan  
Patented honeycomb drum with unique structured surface to protect laundry, rounded SoftLift ribs  
Electronic PerfectDry residual moisture sensing,  
Drying system with conductivity monitoring and patented compensation  
Diagonal airflow for extended contact with laundry

**Interfaces**

7-pole interface for connection of payment systems  
Optical service interface  
Communication slot for retrofitting of interfaces  
e.g. communication module with RS 232 interface

**Design**

Robust spaceframe casing  
Front and lid in stainless steel, side panels in Octoblue, powder-coated  
Galvanised rear panel  
Large porthole door (37 cm dia.)

**Measurements / Weight**External dimensions H / W / D [mm]: 1020/700/727  
Net weight [kg]: 82**Sound emissions**

Drying [dB re 1 pW]: 82

**Test certificates**

VDE, EMC

**Optional accessories**

Plinths  
Laundry trolleys and baskets